

REMARKS

The present invention is a method of wirelessly transmitting data signals to one of a plurality of mobile stations each of which can sense the transmitted signal, a method of operating a mobile station for the reception of data signals and a mobile station including receiving means and processing means, wherein the processing means is configured for controlling the mobile station to perform a method in accordance with the invention. With the invention, a code identifying a destination mobile processor is included in each of a plurality of bursts at a predetermined location therein which permits a base transceiver station to identify the transmitting mobile station from the received signal. See paragraphs [0062] - [0063] of the specification.

Claims 1-7 stand rejected under 35 U.S.C. §102 as being anticipated by United States Patent 6,707,808 (Vedrine). This ground of rejection is traversed for the following reasons.

Claim 1 recites in part: "transmitting a radio block, comprising a plurality of bursts conveying data belonging to a plurality of data streams to said mobile station; and wherein said code is included at each of said bursts at a predetermined location" and claim 4 recites, in part: "receiving a burst of a radio block, the radio block comprising a plurality of bursts and conveying data belonging to a plurality of data streams, to said mobile station; and extracting a code from a predetermined location in said burst and decoding said radio block if the extracted code matches said locally unique code." This subject matter is not taught by Vedrine for the following reasons.

Column 5, lines 26-67, of Vedrine describe a data transmission sequence in which RLC blocks 1-n, each of which contain four bursts, are encoded into particular time slots of a TDMA frame. Each of the RLC blocks 42 contains a temporary flow identifier TFI that corresponds to the temporary block flow TBF. Each block is mapped into bursts 46 which are transmitted over the air interface 28. It is further stated in column 5, lines 54-56, that the receiving mobile stations that are assigned to time slot 2 "decode the four bursts 46 to identify the TFI for the RLC block 42". It is therefore seen that the four bursts must be decoded to obtain the TFI.

In contrast, in accordance with the claimed invention, the code is included in each of the said bursts at a predetermined location as recited in claim 1 and the code is extracted from a predetermined location in said burst and decoding said radio block if the extracted code matches said locally unique code as recited in claim 4.

Accordingly, it is submitted that since all four bursts must be in decoded in Vedrine in order to obtain the TFI, there is no code included in each of said bursts at a predetermined location as recited in claim 1 or extracted at a predetermined location in said burst as recited in claim 4.

Moreover, it should be noted that the uplink state flags (USFs) are block encoded, convolution encoded and interleaved and the resulting data structure is mapped into a sequence of four consecutive bursts 46. It is therefore seen that USFs are also not found at a predetermined location in each burst since the USFs are described as being mapped into a sequence of four consecutive bursts 46. Moreover, it is stated in line 57, that "typically, the USF is interleaved over all four of

the bursts 46" which does not suggest a predetermined location in a single burst. Accordingly, the subject matter of independent claims 1 and 4 is not anticipated.

Moreover, the subject matter of the dependent claims defines more specific aspects of the present invention which are also not anticipated.

Moreover, there is no basis in the record why a person of ordinary skill in the art would be led to modify the teachings of Vedrine except by impermissible hindsight.

In view of the foregoing amendments and remarks, it is submitted that each of the claims in the application is in condition for allowance. Accordingly, early allowance thereof is respectfully requested.

To the extent necessary, Applicants petition for an extension of time under 37 C.F.R. §1.136. Please charge any shortage in fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account No. 01-2135 (1076.41046X00) and please credit any excess fees to such Deposit Account.

Respectfully submitted,

ANTONELLI, TERRY, STOUT & KRAUS, LLP



Donald E. Stout
Registration No. 26,422
(703) 312-6600

Attachments

DES:dlh

1076.41046X00**SUBSTITUTE SPECIFICATION****Title: Downlink Access Control****Background of the Invention****Field of the Invention**

[0001] The present invention relates to downlink access control in a mobile communication system.

~~Background to the Invention~~**Description of the Prior Art**

[0002] In the general packet radio service (GPRS) of GSM (Global System for Mobile communications) networks, downlink multiplexing of radio blocks destined for different mobile stations, sharing a basic physical subchannel, is enabled with an identifier called the temporary flow indicator (TFI) included in each radio block. A temporary block flow (IBF) is a physical connection used by to RR Radio Resource) entities to support the unidirectional transfer of LLC PDUs (Low Layer Compatibility Packet Data Units) on shared basic physical subchannels. Each TBF is assigned a TFI, which is unique among concurrent TBFs, by the network.

[0003] The TFI is encoded in the RLC/MAC header in such a way that every mobile station that can receive the radio block can decode the TFI.

[0004] The concept of transport channels is known from UTRAN (Universal mobile Telecommunications System Radio Access Network). Each of these transport channels can carry a bit class having a different quality of service (QoS) requirement. A plurality of transport channels

for the same user can be multiplexed and sent in the same physical subchannel. In such a system, each radio block may carry one or more TBFs which means that including TFIs in RLC/MAC headers is not a practical way of identifying the mobile station to which a radio block is destined.

Summary of the Invention

[0005] According to the present invention, there is provided a method of wirelessly transmitting data signals to one of a plurality of mobile stations, each of which can sense the transmitted signal, the method comprising:

- allocating a locally unique code to a destination mobile station; and
- transmitting a radio block, comprising a plurality of bursts and conveying data belonging to a plurality of data streams, to said mobile station,

wherein said code is included in each of said bursts at a predetermined location therein.

[0006] Preferably, said location is static.

[0007] Preferably, a method according to the present invention includes transmitting a further radio block, comprising a plurality of bursts and conveying data belonging to a plurality of data streams, to said mobile station, wherein said code is included in each of said bursts at another predetermined location therein to indicate that said mobile station may transmit in the next uplink radio block.

[0008] According to the present invention, there is also provided a method of operating a mobile station for the reception of data signals, the method comprising:-

- receiving a locally unique code;
- receiving a burst of a radio block, the radio block comprising a plurality of bursts and conveying data belonging to a plurality of data streams, to said mobile station; and

extracting a code from a predetermined location in said burst and decoding said radio block if the extracted code matches said locally unique code.

[0009] According to the present invention, there is method of operating a mobile station comprising performing a data reception method according to the present invention, and transmitting a radio block comprising a plurality of bursts, each burst containing said extracted code in a predetermined location.

[0010] According to the present invention, there is further provided a mobile station including receiving means and processing means, wherein the processing means is configured for controlling the mobile station to perform a method according to the present invention.

Brief Description of the Drawings

[0011] ~~Figure Fig.~~ 1 shows a mobile communication system according to the present invention;

[0012] ~~Figure Fig.~~ 2 is a block diagram of a mobile station;

[0013] ~~Figure Fig.~~ 3 is a block diagram of a base transceiver station;

[0014] ~~Figure Fig.~~ 4 illustrates the frame structure used in an embodiment of the present invention;

[0015] ~~Figure Fig.~~ 5 illustrates a packet data channel in an embodiment of the present invention;

[0016] ~~Figure Fig.~~ 6 illustrates the sharing of a radio channel between two half-rate packet channels in an embodiment of the present invention;

[0017] ~~Figure Fig.~~ 7 illustrates the lower levels of a protocol stack used in an embodiment of the present invention;

[0018] ~~Figure Fig.~~ 8 illustrates the generation of a radio signal by a first embodiment of the present invention;

[0019] ~~Figure Fig.~~ 9 illustrates a data burst generated by a first embodiment of the present invention;

[0020] ~~Figure Fig.~~ 10 illustrates the generation of a radio signal by a second embodiment of the present invention; and

[0021] ~~Figure Fig.~~ 11 illustrates part of a reception process adapted for receiving signals produced by the second embodiment of the present invention.

Detailed Description of the Preferred Embodiment

[0022] A preferred embodiment of the present invention will now be described, by way of example, with reference to the accompanying drawings.

[0023] Referring to ~~Figure Fig.~~ 1, a mobile phone network 1 comprises a plurality of switching ~~centres-centers~~ including first and second switching centres 2a, 2b. The first switching ~~centre-center~~ 2a is connected to a plurality of base station controllers including first and second base station controllers 3a, 3b. The second switching ~~centre-center~~ 2b is similarly connected to a plurality of base station controllers (not shown).

[0024] The first base station controller 3a is connected to and controls a base transceiver station 4 and a plurality of other base transceiver stations. The second base station controller 3b is similarly connected to and controls a plurality of base transceiver stations (not shown).

In the present example, each base transceiver station services a respective cell. Thus, the base transceiver station 4 services a cell 5. However, a plurality of cells may be serviced by one base transceiver station by means of directional antennas. A plurality of mobile stations 6a, 6b are

5

located in the cell 5. It will be appreciated what the number and identities of mobile stations in any given cell will vary with time.

[0025] The mobile phone network 1 is connected to a public switched telephone network 7 by a gateway switching ~~centre~~ center 8.

[0026] A packet service aspect of the network includes a plurality of packet service support nodes (one shown) 9 which are connected to respective pluralities of base station controllers 3a, 3b. At least one packet service support gateway node 10 connects the or each packet service support node 10 to the Internet 11.

[0027] The switching ~~centres~~ centers 3a, 3b and the packet service support nodes 9 have access to a home location register 12.

[0028] Communication between the mobile stations (6a, 6b and the base transceiver station 4 employs a time-division multiple access ~DMA) scheme.

[0029] Referring to ~~Figure~~ Fig. 2, the first mobile station 6a comprises an antenna 101, an rf subsystem 102, a baseband DSP (digital signal processing) subsystem 103, an analogue audio subsystem 104, a loudspeaker 105, a microphone 106, a controller 107, a liquid crystal display 108, a keypad 109, memory 110, a battery 111 and a power supply circuit 112.

[0030] The rf subsystem 102 contains if and rf circuits of the mobile telephone's transmitter and receiver and a frequency synthesizer for tuning the mobile station's transmitter and receiver. The antenna 101 is coupled to the rf subsystem 102 for the reception and transmission of radio waves.

[0031] The baseband DSP subsystem 103 is coupled to the rf subsystem 102 to receive baseband signals therefrom and for sending baseband modulation signals thereto. The baseband DSP subsystems 103 includes codec functions which are well-known in the art.

[0032] The analogue audio subsystem 104 is coupled to the baseband DSP subsystem 103 and receives demodulated audio therefrom. The analogue audio subsystem 104 amplifies the demodulated audio and applies it to the loudspeaker 105. Acoustic signals, detected by the microphone 106, are pre-amplified by the analogue audio subsystem 104 and sent to the baseband DSP subsystem 4 for coding.

[0033] The controller 107 controls the operation of the mobile telephone. It is coupled to the rf subsystem 102 for supplying tuning instructions to the frequency synthesizer and to the baseband DSP subsystem 103 for supplying control data and management data for transmission. The controller 107 operates according to a program stored in the memory 110. The memory 110 is shown separately from the controller 107. However, it may be integrated with the controller 107.

[0034] The display device 108 is connected to the controller 107 for receiving control data and the keypad 109 is connected to the controller 107 for supplying user input data signals thereto.

[0035] The battery 111 is connected to the power supply circuit 112 which provides regulated power at the various voltages used by the components of the mobile telephone.

[0036] The controller 107 is programmed to control the mobile station for speech and data communication and with application programs, ~~e.g. for example,~~ a WAP browser, which makes use of the mobile station's data communication capabilities.

[0037] The second mobile station 6b is similarly configured.

[0038] Referring to ~~Figure~~ Fig. 3, greatly simplified, the base transceiver station 4 comprises an antenna 201, an rf subsystem 202, a baseband DSP (digital signal processing) subsystem 203, a base station controller interface 204 and a controller 207.

[0039] The rf subsystem 202 contains the if and rf circuits of the base transceiver station's transmitter and receiver and a frequency synthesizer for tuning the base transceiver station's transmitter and receiver. The antenna 201 is coupled to the rf subsystem 202 for the reception and transmission of radio waves.

[0040] The baseband DSP subsystem 203 is coupled to the rf subsystem 202 to receive baseband signals therefrom and for sending baseband modulation signals thereto. The baseband DSP subsystems 203 includes codec functions which are well-known in the art.

[0041] The base station controller interface 204 interfaces the base transceiver station 4 to its controlling base station controller 3a.

[0042] The controller 207 controls the operation of the base transceiver station 4. It is coupled to the if subsystem 202 for supplying tuning instructions to the frequency synthesizer and to the baseband DSP subsystem for supplying control data and management data for transmission. The controller 207 operates according to a program stored in the memory 210.

[0043] Referring to ~~Figure~~ Fig. 4, each TDMA frame, used for communication between the mobile stations 6a, 6b and the base transceiver stations 4, comprises eight 0.577ms time slots. A

"26 multiframe" comprises 26 frames and a "51 multiframe" comprises 51 frames. Fifty one "26 multiframe" or twenty six "51 multiframe" make up one superframe. Finally, a hyperframe comprises 2048 superframes.

[0044] The data format within the time slots varies according to the function of a time slot. A normal burst, i.e. time slot, comprises three tail bits, followed by 58 encrypted data bits, a 26-bit training sequence, another sequence of 58 encrypted data bits and a further three tail bits. A guard period of eight and a quarter bit durations is provided at the end of the burst. A frequency correction burst has the same tail bits and guard period. However, its payload comprises a fixed 142 bit sequence. A synchronization burst is similar to the normal burst except that the encrypted data is reduced to two clocks of 39 bits and the training sequence is replaced by a 64-bit synchronization sequence. Finally, an access burst comprises eight initial tail bits, followed by a 41-bit synchronization sequence, 36 bits of encrypted data and three more tail bits. In this case, the guard period is 68.25 bits long.

[0045] When used for circuit-switched speech traffic, the ~~channelisation~~ channelization scheme is as employed in GSM.

[0046] Referring to ~~Figure Fig. 5~~, full rate packet switched channels make use of 12 4-slot radio blocks spread over a "51 multiframe". Idle slots follow the third, sixth, ninth and twelfth radio blocks.

[0047] Referring to ~~Figure Fig. 6~~, for half rate, packet switched channels, both dedicated and shared, slots are allocated alternately to two sub-channels.

[0048] The baseband DSP subsystems 103, 203 and controllers 107, 207 of the mobile stations 6a, 6b and the base transceiver stations 4 are configured to implement two protocol stacks. The first protocol stack is for circuit switched traffic and is substantially the same as employed in conventional GSM systems. The second protocol stack is for packet switched traffic.

[0049] Referring to ~~Figure~~ Fig. 7, the layers relevant to the radio link between a mobile station 6a, 6b and a base station controller 4 are the radio link control layer 401, the medium access control layer 402 and the physical layer 403.

[0050] The radio link control layer 401 has two modes: transparent and non-transparent. In transparent mode, data is merely passed up or down through the radio link control layer without modification.

[0051] In non-transparent mode, the radio link control layer 401 provides link adaptation and constructs data blocks from data units received from higher levels by segmenting or concatenating the data units as necessary and performs the reciprocal process for data being passed up the stack. It is also responsible for detecting lost data blocks or reordering data block for upward transfer of their contents, depending on whether acknowledged mode is being used. This layer may also provide backward error correction in acknowledged mode.

[0052] The medium access control layer 402 is responsible for allocating data blocks from the radio link control layer 401 to appropriate transport channels and passing received radio blocks from transport channels to the radio link control layer 403.

[0053] The physical layer 403 is responsible to creating transmitted radio signals from the data passing through the transport channels and passing received data up through the correct transport channel to the medium access control layer 402.

[0054] Referring to Figure Fig. 8, data produced by applications 404a, 404b, 404c propagates down the protocol stack to the medium access control layer 402. The data from the applications 404a, 404b, 404c can belong to any of a plurality of classes for which different qualities of service are required. Data belonging to a plurality of classes may be produced by a single application. The medium access control layer 402 directs data from the applications 404a, 404b, 404c to different transport channels 405, 406, 407 according to class to which it belongs.

[0055] Each transport channel 405, 406, 407 can be configured to process signals according to a plurality of processing schemes 405a, 405b, 405c, 406a, 406b, 406c, 407a, 407b, 407c. The configuration of the transport channels 405, 406, 407 is established during call setup on the basis of the capabilities of the mobile station 6a, 6b and the network and the nature of the application or applications 404a, 404b, 404c being run.

[0056] The processing schemes 405a, 405b, 405c, 406a, 406b, 406c, 407a, 407b, 407c are unique combinations of cyclic redundancy check 405a, 406a, 407a, channel coding 405b, 406b, 407b and rate matching 405c, 406c, 407c. These unique processing schemes will be referred to as "transport formats". An interleaving scheme 405d, 406d, 407d may be selected for each transport channel 405, 406, 407. Thus, different transport channels may use different interleaving schemes and, in alternative embodiments, different interleaving schemes may be used at different times by the same transport channel.

[0057] The combined data rate produced for the transport channels 405, 406, 407 must not exceed that of physical channel or channels allocated to the mobile station 6a, 6b. This places a limit on the transport format combinations that can be permitted. For instance, if there are three transport formats TF1, TF2, TF3 for each transport channel, the following combinations might be valid:-

TF1 TF1 TF2

TF1 TF3 TF3

but not

TF1 TF2 TF2

TF1 TF1 TF3

[0058] The data output by the transport channel interleaving processes are multiplexed by a multiplexing process 410 and then subject to further interleaving 411.

[0059] A transport format combination indicator is generated by a transport format combination indicator generating process 412 from information from the medium access control layer and coded by a coding process 413. The transport format combination indicator is inserted into the data stream by a transport format combination indicator insertion process after the further interleaving 411. The transport format combination indicator is spread across one radio block with portions placed in fixed positions in each burst, on either side of the training symbols (Figure Fig. 9) in this example. The complete transport format combination indicator therefore occurs at fixed intervals, i.e. the block length 20ms. This makes it possible to ensure transport format combination indicator detection when different interleaving types are used e.g. 8 burst diagonal and 4 burst rectangular interleaving. Since the transport format combination indicator is not subject to variable interleaving, it can be readily located by the receiving station and used to control processing of the received data.

[0060] The location of data for each transport channel within the multiplexed bit stream can be determined by a received station from the transport format combination indicator and knowledge of the multiplexing process which is deterministic.

[0061] In the foregoing, the physical channel or subchannel is dedicated to a particular mobile station for a particular call. When physical channels and subchannels are shared, it is necessary for a mobile stations to know when it has access to the uplink. For this purpose, in shared channel operation, uplink state flags are included in each downlink radio block. This flag indicates to the receiving mobile station whether it may start sending data in the next uplink radio block. For compatibility with GPRS and EGPRS mobile stations, the uplink status flags preferably occupy the same bit positions as are specified for EGPRS, e g data bits 150, 151, 168, 169, 171, 172 174, 175, 177, 178 and 195 of each 348-data-bit burst when 8PSK modulation is used. When GMSK modulation is used the situation is more complicated in that different bit positions are used in different burst, albeit in an overall cyclical manner. More particularly, in a four burst cycle, bits 0, 51, 56, 57, 58 and 100 are used in the first burst, bits 35, 56, 57, 58, 84 and 98 are used in the second burst, bits 19, 56, 57, 58, 68 and 82 are used in the third burst and bits 3, 52, 56, 57, 58 and 66 are used in the fourth burst.

[0062] Similarly, downlink status flags are included in downlink -radio bursts to indicate which mobile station a burst is intended for. These flags always have the same position within bursts so that a receiving mobile station can easily locate them. In the preferred embodiment, the uplink and downlink flags have the same mapping onto mobile stations 6a, 6b.

[0063] A mobile station 6a, 6b using a shared subchannel includes its identifier, which is used for the above-described uplink and downlink access control, in its own transmission. Again, this

identifier is located in a predetermined position within each burst. Although the network will generally know the identity of the transmitting mobile station 6a, 6b because it scheduled the transmission, corruption of transmissions from the base transceiver station could result in the wrong mobile station transmitting. Including the identifier in this way enables the base transceiver station to identify the transmitting mobile station from the received signal and then decode the current block, starting by reading the transport format combination indicator and then selecting the correct transport channel decoding processes in dependence on the identity of the transmitting mobile station 6a, 6b and the decoded transport format combination indicator.

[0064] Referring to ~~Figure Fig.~~ 10, in another embodiment, the medium access control layer 402 can support a plurality of active transport format combination sets 501, 502. Each transport format combination set 501, 502 is applicable to transmission according to a different modulation technique, e.g. GMSK and 8PSK. All of the active transport format combination sets 501, 502 are established at call set up.

[0065] Signals in a control channel from the network to a mobile station 6a, 6b cause the mobile station 6a, 6b to switch modulation techniques and, consequently, transport format combination sets 501, 502. The control signals can be generated in response to path quality or congestion levels. The mobile station 6a, 6b may also unilaterally decide which modulation technique to employ.

[0066] Referring to ~~Figure Fig.~~ 11, at a receiving station, be it a mobile station 6a, 6b or a base transceiver station 4, a received signal is applied to demodulating processes 601, 602 for each modulation type. The results of the demodulating processes 601, 602 are ~~analysed~~ analyzed at 603, 604 to determine which modulation technique is being employed and then the transport format

14

combination indicator is extracted 605 from the output of the appropriate demodulated signal and used to control further processing of the signal.

[0067] It will be appreciated that the above-described embodiments may be modified in many ways without departing from the spirit and scope of the claims appended hereto.

Abstract

In a TDMA packet mobile communication system employing the concept of transport channels in a medium access control layer, an downlink access control signal, for identifying a destination mobile station, is inserted into each burst in a predetermined manner. .